



The Falcon 1220 Finishing screen is a compact easily transportable machine that offers operators high productivity, efficient screening.

The Falcon 1220 combines scalping, screening and stockpiling into one self contained unit. Its rugged design enables it to handle materials such as sand and gravel, crushed stone, coal, topsoil and demolition waste.

Remote tipping reject grid, hydraulic screen tensioning of bottom deck mesh and three on-board hydraulic folding conveyors are standard, with optional double deck vibrating grid.

1

HOPPER/FEEDER

- 8m³ (10.5yd³) Hopper Capacity
- 1.05m (42") wide belt feede
- Variable speed

2

SCREEN

- Top deck: 3.66m x 1.53m (12' x 5')
- Bottom deck: 3m x 1.53m (10' x 5')
- Variable screen angle

3

ENGINE OPTIONS

- Tier 3 CAT C4.4
 Engine Power: 83kW (111.3Hp)

 Engine Speed: 2200rpm
- Stage 3A (EU Region Only) CAT C4.4 Engine Power: 98.1kW (131Hp) Engine Speed: 1800rpm
- Tier 3 Option CAT C4.4 LRC (Optional)
 Engine Power: 97kW (130Hp)
 Engine Speed: 2200rpm
- Tier 4 Final CAT C4.4
 Engine Power: 82kW (110Hp)
 Engine Speed: 2200rpm
- Stage V (EU Region Only) CAT C4.4 Engine Power: 102kW (137Hp) Engine Speed: 2200rpm

4

CONVEYORS

- 1m (40") wide mair conveyor
- 1.2m (48") wide fines conveyor with standard discharge height of 3.86m (12' 8")
- 650mm (26") wide Mid-grade conveyor with max 4.86m (15' 11") discharge height
- 650mm (26") wide Over-size conveyor with max 4.86m (15' 11") discharge height

5

TIPPING GRID

- 4.25m (14ft) long tipping grid as standard
- Feed in width 4.77m (15' 8")

6

CONTROL SYSTEM

Simple intuitive operation









EASY TO OPERATE



ENGINE POWER

Tier 4: 82kW / 110Hp



HYDRAULIC TENSIONING OF BOTTOM DECK




QUICK **SETUP** TIME



IDEAL FOR URBAN USE



EASY TO TRANSPORT





RECORD, DISPLAY AND ANALYSE DATA





200 Coalisland Road, Dungannon, Co. Tyrone, BT714DR **Tel:** +442887718500 Email: evoquip@terex.com

